PRODUCT INFORMATION PACKET

genteq®

Model No: 3005 Catalog No: 3005

1/3 HP OEM Replacement Motor, 825 RPM, 230 Volts, 48 Frame, Semi Enclosed

HVAC/R OEM Replacement Motors





Regal and Genteq are trademarks of Regal Beloit Corporation or one of its affiliated companies.

©2019 Regal Beloit Corporation, All Rights Reserved. MC017097E

Product Information Packet: Model No: 3005, Catalog No:3005 1/3 HP OEM Replacement Motor, 825 RPM, 230 Volts, 48 Frame, Semi Enclosed



Nameplate Specifications

Output HP	1/3 Hp	Frequency	60 Hz
Voltage	230 V	Current	2.40 A
Speed	825 rpm	Service Factor	1
Phase	1	Duty	Continuous Air Over
Insulation Class	В	Frame	48
Enclosure	Open Air Over	Thermal Protection	Thermally Protected
Ambient Temperature	40 °C	UL	Recognized
CSA	Υ	CE	N

Technical Specifications

Electrical Type	Permanent Split Capacitor	Poles	8	
Rotation	Clockwise	Mounting	Round	
Motor Orientation	Any	Drive End Bearing	Ball	
Opp Drive End Bearing	Ball	Frame Material	Rolled Steel	
Shaft Type	Double Flat	Overall Length	9.81 in	
Frame Length	4.57 in	Shaft Diameter	0.500 in	
Shaft Extension	3.92 in			

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:25/10/2019

This document is the property of RESAL-BELOTT Corporation (1987) including its subsidiaries and distinct and contains proprietary information of REC. This document is loaned on the express condition that neither it nor the information contained there in shall be disclosed to others without the express written content of REC, and that the information shall be used by the recipilist only as approved expressly by REC. The document shall be returned to REC upon its request. This document may be subject to certain restrictions under the U.S. export control law and requiations.


REV REVISIONS DESCRIPT]

9

JAR 2-2005

-Convert to RBC Format

-1.40 MAX



8

3 of 3

∃é⊁T FACE:

⇧

COLORS OR NUMBERS DENOTING LEAD IDENTIFICATION AND N.P. NUMBER ARE TO BE 18 POINT NEWS GOTHIC CONDENSED. OTHER INFORMATION SHOULD BE 18 POINT IF SPACE ALLOWS, OTHERW USE 14 POINT. OTHERWISE OTHER

MATERIALS: 4 MIL WHITE VINYL ADHESIVE STOCK GE SPEC A50FG41-S1

BLACK INK GE SPEC A50FM48

NOTE: THE BOX LINES AND DIMENSIONS REPRESENT THE SIZE OF THE TAPE TO BE USED. DO NOT INCLUDE THESE IN STAMP FORMAT.



REGAL-BELOIT CORPORATION

CONNECTION DIAGRAM **danss** (

RLC

NP24X327048

NO