PRODUCT INFORMATION PACKET

Model No: 3160 Catalog No: 3160 1/6 HP OEM Replacement Motor, 1075 RPM, 2 Speed, 208-230 Volts, 48 Frame, OAO HVAC/R OEM Replacement Motors





Regal and Genteq are trademarks of Regal Beloit Corporation or one of its affiliated companies. ©2019 Regal Beloit Corporation, All Rights Reserved. MC017097E





Product Information Packet: Model No: 3160, Catalog No:3160 1/6 HP OEM Replacement Motor, 1075 RPM, 2 Speed, 208-230 Volts, 48 Frame, OAO



Nameplate Specifications

| Output HP | 1/6 Hp | Frequency | 60 Hz | |
|----------------------------------|------------------------|-----------------------|-----------------------------------|--|
| Voltage | 208-230 V | Current | 1.20 A | |
| Speed | 1075 rpm | Service Factor | 1 | |
| Phase | 1 | Duty | Continuous Air Over | |
| Insulation Class | В | Frame | 48 | |
| | | | Thermally Protected | |
| Enclosure | Open Air Over | Thermal Protection | Thermally Protected | |
| Enclosure Ambient Temperature | Open Air Over 40 °C | Thermal Protection UL | Thermally Protected Recognized | |

Technical Specifications

| Electrical Type | Permanent Split Capacitor | Poles | 6 | |
|-----------------------|---------------------------|-------------------|--------------|--|
| Rotation | Counterclockwise | Mounting | Lug | |
| Motor Orientation | Vertical Shaft Up | Drive End Bearing | Sleeve | |
| Opp Drive End Bearing | Sleeve | Frame Material | Rolled Steel | |
| Shaft Type | Flat | Overall Length | 7.38 in | |
| Frame Length | 3.07 in | Shaft Diameter | 0.500 in | |
| Shaft Extension | 2.75 in | | | |

This is an uncontrolled document once printed or downloaded and is subject to change without notice. Date Created:25/10/2019

| | approved expressivy by NBC Ars refurned to NBC upon its request | io. The docume | al shoii Ge | |
|---------|--|-------------------|-------------|---------------|
| | | | | -1.40— МАХ |
| ON OMO | | | | |
| Ma | | | | |
| ۶Ł | | | | \sim |
| €) A | <u> </u> BF | ROWN | | —(4 F) |
| | | | | - |
| | | WHITE O | R YEL | |
| | | | | |
| | | BLACK | H] | |
| | -†* | | | |
| | | RED | LO | |
| | | | | <u> </u> |
| | | | | |
| ~ |] / | | | |
| ~ | NF | [,] 2195 | 524 | |
| | | | | |
| | | | | |
| | NOTE: THIS DR MOTOR N | }AW]NG JAMEPLA | W]LL BE | E ELECTI |
| | | | | |
| | UNLESS OTHERWISE SPECIFIED | SIGNA | | DATE |
| | DIMENSIONS ARE IN INCHES TOLEPANCES ON: | DRAWN | FA ROSS | 1959 |
| | 2 PL DECIMALS ± 3 PL DECIMALS ± | CHECKED | | |
| | ANGLES 1 . / | ENGRG | | |
| | | 1 220ED | | |
| | NATERIAL : | | | |
| | | CAD NO | | |
| | APPLIED PRACTICES | | | |
| | F39:XNP8 | <u> </u> | | |
| | · bai//ii a | | | |
| \sim | | | | |