P
TYPE
GE SIZE
NEMA FR
C
K
L
N
N–W
1
K KH
32
48
8.99
1.25
3.71
1.50
1.63/1.41
W* IS A CLEARANCE DUE TO VARIATION IN PARTS AND ASSEMBLY.
.180 R. REF.
VIEW SHOWING P.E. VENTILATION OPENINGS
5.66
5.58
2.12
2.12
.69
.72
3.00 2.97 SOLID
3.00 2.94 RESIL.
.102
5.83 MAX.
5.61 MAX.
.500-14 CONDUIT THREAD
1.95
1.83
3.01
2.99
2.17
2.15
3.57
3.45
1.380
1.370
1.380
1.370
.370
.340
2.50
.5000
.4995
.05 X (K) LG. FLAT
W*
N–W
N MIN.
L MAX.
3.78 MAX.
C MAX.
REGAL-BELOIT CORPORATION
TITLE
OUTLINE
FORM N-GENERAL PURPOSE MOTOR-DRIP PROOF-SOLID OR RESIL BASE-BALL OR SLEEVE BEARING-SPECIAL MOUNTING HOLES IN BASE
SIZE A
DRAWING
52A1112851
REV 1
SCALE: 0.250
REF. No:
SHEET 1 # 1
SOLID MODEL: 52A1112851
MATERIAL
DIMENSIONS ARE IN INCHES
PRACTICES
APPLIED
FOR ADDITIONAL INFO REFER TO:
QUALITY
MFG
CHKRG
CHECKED
DETAIL
MODEL DURGA 03/31/05
SIGNATURES DATE
ISSUED DURGA 03/31/05
REVISIONS
REV. DESCRIPTION DATE APPROVED
1 CHG TO RBC FORMAT PER ISO5-1777 04/28/06 MADHU
THIRD ANGLE PROJECTION
SIZE A
DRAWING NO. 52A1112851
REV 1
SHEET 1