

## Nameplate Specifications

Output HP	<b>1,0.33 Hp</b>	Output KW	<b>0.75 kW</b>
Frequency	<b>60 Hz</b>	Voltage	<b>115 V</b>
Current	<b>11.5,7 A</b>	Speed	<b>1725,1140 rpm</b>
Service Factor	<b>1.15</b>	Phases	<b>1</b>
Efficiency	<b>74 %</b>	Duty	<b>CONTINUOUS</b>
Insulation Class	<b>B</b>	Design Code	<b>2VT</b>
KVA Code	<b>H</b>	Frame	<b>56</b>
Enclosure	<b>DP</b>	Overload Protector	<b>AUTOMATIC</b>
Ambient Temperature	<b>40 °C</b>	Drive End Bearing Size	<b>6203</b>
Opp Drive End Bearing Size	<b>6203</b>	UL	<b>Recognized</b>
CSA	<b>Y</b>	CE	<b>Y</b>
IP Code	<b>22</b>		

## Technical Specifications

Electrical Type	<b>CAP START CAP RUN</b>	Starting Method	<b>ACROSS THE LINE</b>
Poles	<b>4//6</b>	Rotation	<b>SELECTIVE CCW</b>
Mounting	<b>RESILIENT BASE</b>	Motor Orientation	<b>HORIZONTAL</b>
Drive End Bearing	<b>BALL</b>	Opp Drive End Bearing	<b>BALL</b>
Frame Material	<b>ROLLED STEEL</b>	Shaft Type	<b>T</b>
Overall Length	<b>12.85 in</b>	Frame Length	<b>8.56 in</b>
Shaft Diameter	<b>0.63 in</b>	Shaft Extension	<b>1.91 in</b>
Assembly/Box Mounting	<b>F1 ONLY</b>		