

Nameplate Specifications

| | | | |
|----------------------------|---------------|------------------------|-----------------------|
| Output HP | 0.5 Hp | Output KW | 0.37 kW |
| Frequency | 60 Hz | Voltage | 277 V |
| Current | 3.55 A | Speed | 1725 rpm |
| Service Factor | 1.25 | Phases | 1 |
| Efficiency | 66 % | Duty | CONTINUOUS |
| Insulation Class | B | Design Code | NO DESIGN CODE |
| KVA Code | L | Frame | 56 |
| Enclosure | DP | Overload Protector | NOT |
| Ambient Temperature | 40 °C | Drive End Bearing Size | 6203 |
| Opp Drive End Bearing Size | 6203 | UL | Recognized |
| CSA | Y | CE | N |
| IP Code | 22 | | |

Technical Specifications

| | | | |
|-----------------------|--------------------------------------|-----------------------|------------------------|
| Electrical Type | CAP START IND RUN | Starting Method | ACROSS THE LINE |
| Poles | 4 | Rotation | SELECTIVE CCW |
| Mounting | RESILIENT BASE-EXTENDED STUDS | Motor Orientation | HORIZONTAL |
| Drive End Bearing | BALL | Opp Drive End Bearing | BALL |
| Frame Material | ROLLED STEEL | Shaft Type | T |
| Overall Length | 11.72 in | Frame Length | 7.75 in |
| Shaft Diameter | 0.63 in | Shaft Extension | 1.97 in |
| Assembly/Box Mounting | F1 ONLY | | |