

Nameplate Specifications

| | | | |
|----------------------------|----------------------|------------------------|------------------------------------|
| Output HP | 3 Hp | Output KW | 2.24 kW |
| Frequency | 60 Hz | Voltage | 208-230/460 V |
| Current | 8.9-8.4/4.2 A | Speed | 3450 rpm |
| Service Factor | 1.15 | Phases | 3 |
| Efficiency | 84 % | Duty | CONTINUOUS |
| Insulation Class | B | Design Code | B |
| KVA Code | J | Frame | 56HZ |
| Enclosure | DP | Overload Protector | AUTOMATIC |
| Ambient Temperature | 40 °C | Drive End Bearing Size | 6205 |
| Opp Drive End Bearing Size | 6205 | UL | Recognized (Not Protector) |
| CSA | Y | CE | Y |
| IP Code | 22 | | |

Technical Specifications

| | | | |
|-----------------------|------------------------|-----------------------|------------------------|
| Electrical Type | SQ CAGE IND RUN | Starting Method | ACROSS THE LINE |
| Poles | 2 | Rotation | REV |
| Mounting | RESILIENT BASE | Motor Orientation | HORIZONTAL |
| Drive End Bearing | BALL | Opp Drive End Bearing | BALL |
| Frame Material | ROLLED STEEL | Shaft Type | SGL SPL EXT |
| Overall Length | 12.22 in | Frame Length | 7.56 in |
| Shaft Diameter | 0.63 in | Shaft Extension | 2.28 in |
| Assembly/Box Mounting | F1 ONLY | | |