

PRODUCT INFORMATION PACKET

Modal No: 5KC38NN410X
Catalog No: C1155
3/4,3450,DP,56,1/60/115/208-230
Open Drip Proof (ODP)



Regal and Marathon are trademarks of Regal Beloit Corporation or one of its affiliated companies.
©2017 Regal Beloit Corporation, All Rights Reserved. MC017097E



Nameplate Specifications

Output HP	0.75 Hp	Output KW	0.56 kW
Frequency	60 Hz	Voltage	115/208-230 V
Current	10.0,4.9-5.0 A	Speed	3450 rpm
Service Factor	1.25	Phases	1
Efficiency	68 %	Duty	CONT
Insulation Class	B	Design Code	-
KVA Code	K	Frame	56
Enclosure	DP	Overload Protector	AUTO
Ambient Temperature	40 °C	Drive End Bearing Size	6203
Opp Drive End Bearing Size	6203	UL	Recognized
CSA	Yes	CE	N

Technical Specifications

Electrical Type	Capacitor start(CSIR)	Starting Method	SM
Poles	2	Rotation	CCW/CW
Mounting	RB	Motor Orientation	ANY
Drive End Bearing	BALL	Opp Drive End Bearing	BALL
Frame Material	Rolled Steel	Overall Length	11.32 in
Frame Length	7.22 in	Shaft Diameter	0.63 in
Shaft Extension	1.88 in		

