

Nameplate Specifications

| | | | |
|----------------------------|----------------------|------------------------|----------------------|
| Output HP | 0.5 Hp | Output KW | 0.37 kW |
| Frequency | 60 Hz | Voltage | 115/208-230 V |
| Current | 8.6,4.1-4.3 A | Speed | 1725 rpm |
| Service Factor | 1.15 | Phases | 1 |
| Efficiency | 64.9 % | Duty | CONT |
| Insulation Class | B | Design Code | - |
| KVA Code | M | Frame | 56 |
| Enclosure | TEFC | Overload Protector | N/R |
| Ambient Temperature | 40 °C | Drive End Bearing Size | 6203 |
| Opp Drive End Bearing Size | 6203 | UL | Recognized |
| CSA | Yes | CE | N |

Technical Specifications

| | | | |
|-------------------|------------------------------|-----------------------|----------------|
| Electrical Type | Capacitor start(CSIR) | Starting Method | SM |
| Poles | 4 | Rotation | CCW/CW |
| Mounting | WB | Motor Orientation | ANY |
| Drive End Bearing | BALL | Opp Drive End Bearing | BALL |
| Frame Material | Rolled Steel | Overall Length | 11 in |
| Frame Length | 5.72 in | Shaft Diameter | 0.63 in |
| Shaft Extension | 1.88 in | | |