

Nameplate Specifications

| | | | |
|------------------------|-------------------|----------------------------|------------------|
| Output HP | 0.75 Hp | Output KW | 0.56 kW |
| Frequency | 50 Hz | Voltage | 110/220 V |
| Current | 12.2,6.1 A | Speed | 1425 rpm |
| Service Factor | 1.25 | Phases | 1 |
| Efficiency | 68 % | Duty | CONT |
| Insulation Class | B | KVA Code | M |
| Frame | 56 | Enclosure | DP |
| Overload Protector | AUTO | Ambient Temperature | 40 °C |
| Drive End Bearing Size | 6203 | Opp Drive End Bearing Size | 6203 |
| UL | Recognized | CSA | Yes |
| CE | N | | |

Technical Specifications

| | | | |
|-------------------|------------------------------|-----------------------|-----------------|
| Electrical Type | Capacitor start(CSIR) | Starting Method | SM |
| Poles | 4 | Rotation | CCW/CW |
| Mounting | RB | Motor Orientation | ANY |
| Drive End Bearing | BALL | Opp Drive End Bearing | BALL |
| Frame Material | Rolled Steel | Overall Length | 11.38 in |
| Frame Length | 7.15 in | Shaft Diameter | 0.63 in |
| Shaft Extension | 1.88 in | | |