

## Nameplate Specifications

Output HP	<b>1.5 Hp</b>	Output KW	<b>1.12 kW</b>
Frequency	<b>60 Hz</b>	Voltage	<b>115/230 V</b>
Current	<b>16.4,8.2 A</b>	Speed	<b>3450 rpm</b>
Service Factor	<b>1.3</b>	Phases	<b>1</b>
Efficiency	<b>74 %</b>	Duty	<b>CONT</b>
Insulation Class	<b>B</b>	KVA Code	<b>H</b>
Frame	<b>143T</b>	Enclosure	<b>TENV</b>
Overload Protector	<b>AUTO</b>	Ambient Temperature	<b>40 °C</b>
Drive End Bearing Size	<b>6205</b>	Opp Drive End Bearing Size	<b>6203</b>
UL	<b>Recognized</b>	CSA	<b>Yes</b>
CE	<b>N</b>		

## Technical Specifications

Electrical Type	<b>Capacitor start(CSIR)</b>	Starting Method	<b>SM</b>
Poles	<b>2</b>	Rotation	<b>CCW/CW</b>
Mounting	<b>WB</b>	Motor Orientation	<b>ANY</b>
Drive End Bearing	<b>BALL</b>	Opp Drive End Bearing	<b>BALL</b>
Frame Material	<b>Rolled Steel</b>	Overall Length	<b>12.28 in</b>
Frame Length	<b>7.68 in</b>	Shaft Diameter	<b>0.88 in</b>
Shaft Extension	<b>2.25 in</b>		