PRODUCT INFORMATION PACKET

Modal No: 5KCR48TN8062 Catalog No: C194 3,3450,DP,145T,1/60/115/230 Open Drip Proof (ODP)



Regal and Marathon are trademarks of Regal Beloit Corporation or one of its affiliated companies. ©2017 Regal Beloit Corporation, All Rights Reserved. MC017097E



marathon[®] Motors



Nameplate Specifications

Output HP	3 Нр	Output KW	2.24 kW
Frequency	60 Hz	Voltage	115/230 V
Current	29.4,14.7 A	Speed	3450 rpm
Service Factor	1.15	Phases	1
Efficiency	78.5 %	Duty	CONT
Insulation Class	В	KVA Code	J
Frame	145T	Enclosure	DP
Overload Protector	N/R	Ambient Temperature	40 °C
Drive End Bearing Size	6205	Opp Drive End Bearing Size	6203
UL	Recognized	CSA	Yes
CE	Ν		

Technical Specifications

Electrical Type	Capacitor Start Capacitor Run(CSCR)	Starting Method	SM
Poles	2	Rotation	CCW/CW
Mounting	WB	Motor Orientation	ANY
Drive End Bearing	BALL	Opp Drive End Bearing	BALL
Frame Material	Rolled Steel	Overall Length	13.13 in
Frame Length	8.43 in	Shaft Diameter	0.88 in
Shaft Extension	2.25 in		

Uncontrolled Copy

