

Nameplate Specifications

| | | | |
|------------------------|-----------------------|----------------------------|----------------------|
| Output HP | 1.5 Hp | Output KW | 1.12 kW |
| Frequency | 60 Hz | Voltage | 115/208-230 V |
| Current | 16.4,8.4-8.2 A | Speed | 1725 rpm |
| Service Factor | 1.15 | Phases | 1 |
| Efficiency | 77 % | Duty | CONT |
| Insulation Class | B | KVA Code | J |
| Frame | 56H | Enclosure | DP |
| Overload Protector | AUTO | Ambient Temperature | 40 °C |
| Drive End Bearing Size | 6205 | Opp Drive End Bearing Size | 6203 |
| UL | Recognized | CSA | Yes |
| CE | N | | |

Technical Specifications

| | | | |
|-------------------|--|-----------------------|----------------|
| Electrical Type | Capacitor Start Capacitor Run(CSCR) | Starting Method | SM |
| Poles | 4 | Rotation | CCW/CW |
| Mounting | RB | Motor Orientation | ANY |
| Drive End Bearing | BALL | Opp Drive End Bearing | BALL |
| Frame Material | Rolled Steel | Overall Length | 11.9 in |
| Frame Length | 7.68 in | Shaft Diameter | 0.63 in |
| Shaft Extension | 1.88 in | | |