

Nameplate Specifications

| | | | |
|------------------------|-------------------|----------------------------|-----------------|
| Output HP | 0.25 Hp | Output KW | 0.19 kW |
| Frequency | 60 Hz | Voltage | 115 V |
| Current | 5.1 A | Speed | 1725 rpm |
| Service Factor | 1.35 | Phases | 1 |
| Efficiency | 51.9 % | Duty | CONT |
| Insulation Class | B | KVA Code | P |
| Frame | 48Y | Enclosure | OPEN |
| Overload Protector | AUTO | Ambient Temperature | 40 °C |
| Drive End Bearing Size | 6203 | Opp Drive End Bearing Size | 6203 |
| UL | Recognized | CSA | Yes |
| CE | N | | |

Technical Specifications

| | | | |
|-------------------|---------------------|-----------------------|----------------|
| Electrical Type | Split Phase | Starting Method | SM |
| Poles | 4 | Rotation | CW/CCW |
| Mounting | RB | Motor Orientation | ANY |
| Drive End Bearing | BALL | Opp Drive End Bearing | BALL |
| Frame Material | Rolled Steel | Overall Length | 9.78 in |
| Frame Length | 4.91 in | Shaft Diameter | 0.5 in |
| Shaft Extension | 1.5 in | Thru-bolts Extension | 0 |