

## Nameplate Specifications

|                        |                   |                            |                 |
|------------------------|-------------------|----------------------------|-----------------|
| Output HP              | <b>0.33 Hp</b>    | Output KW                  | <b>0.25 kW</b>  |
| Frequency              | <b>60 Hz</b>      | Voltage                    | <b>115 V</b>    |
| Current                | <b>6.2 A</b>      | Speed                      | <b>1725 rpm</b> |
| Service Factor         | <b>1</b>          | Phases                     | <b>1</b>        |
| Efficiency             | <b>58.4 %</b>     | Duty                       | <b>CONT</b>     |
| Insulation Class       | <b>B</b>          | KVA Code                   | <b>T</b>        |
| Frame                  | <b>48Z</b>        | Enclosure                  | <b>DP</b>       |
| Overload Protector     | <b>N/R</b>        | Ambient Temperature        | <b>40 °C</b>    |
| Drive End Bearing Size | <b>0.5</b>        | Opp Drive End Bearing Size | <b>0.5</b>      |
| UL                     | <b>Recognized</b> | CSA                        | <b>Yes</b>      |
| CE                     | <b>N</b>          |                            |                 |

## Technical Specifications

|                   |                     |                       |                 |
|-------------------|---------------------|-----------------------|-----------------|
| Electrical Type   | <b>Split Phase</b>  | Starting Method       | <b>SM</b>       |
| Poles             | <b>4</b>            | Rotation              | <b>CCW/CW</b>   |
| Mounting          | <b>WB</b>           | Motor Orientation     | <b>ANY</b>      |
| Drive End Bearing | <b>BALL</b>         | Opp Drive End Bearing | <b>BALL</b>     |
| Frame Material    | <b>Rolled Steel</b> | Overall Length        | <b>10.36 in</b> |
| Frame Length      | <b>5.16 in</b>      | Shaft Diameter        | <b>0.5 in</b>   |
| Shaft Extension   | <b>1.5 in</b>       |                       |                 |